

MiniSafe REG

The MiniSafe REG as Smart Home control unit receives EnOcean signals from many Eltako sensors and actuators and permits highly encrypted access, both internally and externally, with the Eltako Wireless Building app GFA4 by smartphone or tablet. Smart Home controller.

MiniSafe REG connected to the local network via Ethernet. The intended use of the MiniSafe REG is the bidirectional communication with EnOcean wireless signals over Ethernet (TCP/IP).

Scope of supply: MiniSafe REG, wireless antenna, wall adapter power supply, 1x ethernet cable 2 m RJ45, 2x DIN rail adapters, quick start guide, instruction for downloading the app GFA4.

Specifications: Processor: Intel X1021, memory: 1 GB DDR3 RAM + 4 GB eMMC, LAN: 1x 10/100Mbit ethernet, integrated EnOcean-868MHz wireless module (TCM310) ESP3, power supply 5V, plastic housing gray RAL 7035, dimensions: 165x70x35 mm with slots for wall mounting and feet to put down, weight: 175 grams.

The IP configuration is performed via the app GFA4 from the Android app store or Apple app store.

The enclosed small antenna can be replaced with a wireless antenna FA250 with magnetic base and cable.

Can be mounted on an DIN rail DIN-EN 60715 TH35 with the DIN Rail adapters for the long holes, 10 pitches wide. Instead of the adapter plug, the DIN-rail power supply HDR-30-5 can be used. The special 5V connection cable is already mounted.



5-13

MiniSafe REG	Smart Home control unit	EAN 4010312319017	308,80 €/pc.
FA250	Wireless antenna with 250cm cable, black	EAN 4010312300244	21,10 €/pc.
FA250-gw	Wireless antenna with 250cm cable, grey white	EAN 4010312317051	21,10 €/pc.
HDR-30-5	Power supply unit 5V/15W for MiniSafe REG	EAN 4010312318874	42,10 €/pc.